



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmHO	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH1225S	Sleeve	H	12	6.0	0.40	2400	91.63	2.595	4.87	40.10	•	•	•	•	•	164	60	11.0
RDM1225S				6.0	0.23	2000	76.92	2.178	3.58	33.23	•	•	•	•	•			
RDL1225S				6.0	0.18	1700	65.12	1.844	2.65	31.57	•	•	•	•	•			
RDH1225B	Ball			6.0	0.40	2400	91.63	2.595	4.87	40.10	•	•	•	•	•			
RDM1225B				6.0	0.23	2000	76.92	2.178	3.58	33.23	•	•	•	•	•			
RDL1225B				6.0	0.18	1700	65.12	1.844	2.65	31.57	•	•	•	•	•			
RDH1225S2	Sleeve	24	12.0	0.35	2400	91.63	2.595	4.87	40.10	•	•	•	•	•				
RDM1225S2			12.0	0.20	2000	76.92	2.178	3.58	33.23	•	•	•	•	•				
RDL1225S2			12.0	0.13	1700	65.12	1.844	2.65	31.57	•	•	•	•	•				
RDH1225B2	Ball		12.0	0.35	2400	91.63	2.595	4.87	40.10	•	•	•	•	•				
RDM1225B2			12.0	0.20	2000	76.92	2.178	3.58	33.23	•	•	•	•	•				
RDL1225B2			12.0	0.13	1700	65.12	1.844	2.65	31.57	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V						•

