



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RBH1232B	Ball	B	12	6.0	0.87	2100	33.13	0.938	20.14	47.98	•	•	•	•	•	260	40	11.7
RBM1232B				6.0	0.60	1800	28.23	0.799	13.36	45.34	•	•	•	•	•			
RBL1232B				6.0	0.49	1600	25.07	0.709	9.62	42.42	•	•	•	•	•			
RBH1232B2			24	12.0	0.50	2100	33.13	0.938	20.14	47.98	•	•	•	•	•			
RBM1232B2				12.0	0.35	1800	28.23	0.799	13.36	45.34	•	•	•	•	•			
RBL1232B2				12.0	0.28	1600	25.07	0.709	9.62	42.42	•	•	•	•	•			
RBH1232B4			48	24.0	0.30	2100	33.13	0.938	20.14	47.98	•	•	•	•	•			
RBM1232B4				24.0	0.20	1800	28.23	0.799	13.36	45.34	•	•	•	•	•			
RBL1232B4				24.0	0.15	1600	25.07	0.709	9.62	42.42	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
12V	•	•	•	•
24V	•	•	•	•
48V	•	•	•	•

