



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH1232S	Sleeve	B	12	6.0	0.60	3750	120.48	3.411	10.74	47.14	•	•	•	•	•	250	40	11.0
RDM1232S				6.0	0.50	3300	106.62	3.019	8.63	44.13	•	•	•	•	•			
RDL1232S				6.0	0.32	2900	93.02	2.634	6.90	40.56	•	•	•	•	•			
RDH1232B	Ball			6.0	0.60	3750	120.48	3.411	10.74	47.14	•	•	•	•	•			
RDM1232B				6.0	0.50	3300	106.62	3.019	8.63	44.13	•	•	•	•	•			
RDL1232B				6.0	0.32	2900	93.02	2.634	6.90	40.56	•	•	•	•	•			
RDH1232S2	Sleeve	24	12.0	0.45	3750	120.48	3.411	10.74	47.14	47.14	•	•	•	•	•			
RDM1232S2			12.0	0.28	3300	106.62	3.019	8.63	44.13	44.13	•	•	•	•	•			
RDL1232S2			12.0	0.22	2900	93.02	2.634	6.90	40.56	40.56	•	•	•	•	•			
RDH1232B2	Ball		12.0	0.45	3750	120.48	3.411	10.74	47.14	47.14	•	•	•	•	•			
RDM1232B2			12.0	0.28	3300	106.62	3.019	8.63	44.13	44.13	•	•	•	•	•			
RDL1232B2			12.0	0.22	2900	93.02	2.634	6.90	40.56	40.56	•	•	•	•	•			
RDH1232S4	Sleeve	48	24.0	0.23	3750	120.48	3.411	10.74	47.14	47.14	•	•	•	•	•			
RDM1232S4			24.0	0.18	3300	106.62	3.019	8.63	44.13	44.13	•	•	•	•	•			
RDL1232S4			24.0	0.15	2900	93.02	2.634	6.90	40.56	40.56	•	•	•	•	•			
RDH1232B4	Ball		24.0	0.23	3750	120.48	3.411	10.74	47.14	47.14	•	•	•	•	•			
RDM1232B4			24.0	0.18	3300	106.62	3.019	8.63	44.13	44.13	•	•	•	•	•			
RDL1232B4			24.0	0.15	2900	93.02	2.634	6.90	40.56	40.56	•	•	•	•	•			

SAFETY APPROVALS ( 安規認證 )

	CE	UL	CUL	TUV	VDE
12V	•	•	•	•	
24V	•	•	•	•	•
48V	•	•	•	•	

