



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing		
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs	
RDD1238S	Sleeve	B	12	6.0	6.0	0.60	3000	126.67	3.586	7.83	41.94	•	•	•	•	•	260	40	12.5
RDH1238S				6.0	0.60	2700	113.36	3.210	6.50	40.80	•	•	•	•	•				
RDM1238S				6.0	0.40	2400	100.48	2.845	5.22	36.50	•	•	•	•	•				
RDL1238S				6.0	0.25	2000	83.21	2.356	3.73	31.51	•	•	•	•	•				
RDD1238B	Ball			6.0	0.60	3000	126.67	3.586	7.83	41.94	•	•	•	•	•				
RDH1238B				6.0	0.60	2700	113.36	3.210	6.50	40.80	•	•	•	•	•				
RDM1238B				6.0	0.40	2400	100.48	2.845	5.22	36.50	•	•	•	•	•				
RDL1238B				6.0	0.25	2000	83.21	2.356	3.73	31.51	•	•	•	•	•				
RDD1238S2	Sleeve	24	12.0	0.40	3000	126.67	3.586	7.83	41.94	•	•	•	•	•					
RDH1238S2			12.0	0.40	2700	113.36	3.210	6.50	40.80	•	•	•	•	•					
RDM1238S2			12.0	0.30	2400	100.48	2.845	5.22	36.50	•	•	•	•	•					
RDL1238S2			12.0	0.20	2000	83.21	2.356	3.73	31.51	•	•	•	•	•					
RDD1238B2	Ball		12.0	0.40	3000	126.67	3.586	7.83	41.94	•	•	•	•	•					
RDH1238B2			12.0	0.40	2700	113.36	3.210	6.50	40.80	•	•	•	•	•					
RDM1238B2			12.0	0.30	2400	100.48	2.845	5.22	36.50	•	•	•	•	•					
RDL1238B2			12.0	0.20	2000	83.21	2.356	3.73	31.51	•	•	•	•	•					

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
12V	•	•	•	•	•
24V					

