



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH4028S5	Sleeve	B	5	3.5	0.35	7500	9.42	0.266	6.05	27.43	•	•	•	•	•	36	400	15.4
RDM4028S5				3.5	0.30	6500	8.26	0.233	4.71	24.33	•	•	•	•	•			
RDL4028S5				3.5	0.22	5000	6.12	0.173	3.50	20.30	•	•	•	•	•			
RDH4028B5	Ball			3.5	0.35	7500	9.42	0.266	6.05	27.43	•	•	•	•	•			
RDM4028B5				3.5	0.30	6500	8.26	0.233	4.71	24.33	•	•	•	•	•			
RDL4028B5				3.5	0.22	5000	6.12	0.173	3.50	20.30	•	•	•	•	•			
RDH4028S	Sleeve		12	6.0	0.20	8800	11.25	0.318	8.19	31.44	•	•	•	•	•			
RDM4028S				6.0	0.18	8000	10.14	0.287	6.87	29.09	•	•	•	•	•			
RDL4028S				6.0	0.12	5000	6.12	0.177	3.50	20.30	•	•	•	•	•			
RDH4028B	Ball			6.0	0.20	8800	11.25	0.318	8.19	31.44	•	•	•	•	•			
RDM4028B				6.0	0.18	8000	10.14	0.287	6.87	29.09	•	•	•	•	•			
RDL4028B				6.0	0.12	5000	6.12	0.177	3.50	20.30	•	•	•	•	•			
RDH4028S2	Sleeve	24	12.0	0.16	8800	11.25	0.318	8.19	31.44	•	•	•	•	•				
RDM4028S2			12.0	0.12	8000	10.14	0.287	6.87	29.09	•	•	•	•	•				
RDL4028S2			12.0	0.09	5000	6.12	0.173	3.50	20.30	•	•	•	•	•				
RDH4028B2	Ball		12.0	0.16	8800	11.25	0.318	8.19	31.44	•	•	•	•	•				
RDM4028B2			12.0	0.12	8000	10.14	0.287	6.87	29.09	•	•	•	•	•				
RDL4028B2			12.0	0.09	5000	6.12	0.173	3.50	20.30	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V	•	•	•	•
12V	•	•	•	•
24V	•	•	•	•

