



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing									
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs								
RDH4510S5	Sleeve	E	5	3.5	0.21	6000	8.30	0.235	3.60	30.04	•	•		•	•	15	600	11.8								
RDM4510S5											•	•		•	•											
RDL4510S5											•	•		•	•											
RDH4510B5	Ball										5	3.5	0.21	6000	8.30				0.235	3.60	30.04	•	•		•	•
RDM4510B5																						•	•		•	•
RDL4510B5																						•	•		•	•
RDH4510S	Sleeve	12	6.0	0.10	6000	8.30	0.235	3.60	30.04	•						•		•				•				
RDM4510S										•						•		•				•				
RDL4510S										•						•		•				•				
RDH4510B	Ball									12	6.0	0.10	6000	8.30	0.235	3.60	30.04	•	•		•	•				
RDM4510B																		•	•		•	•				
RDL4510B																		•	•		•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V	•	•	•	•
12V	•	•	•	•

