



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RBH5015S	Sleeve	A	12	6.0	0.14	5000	4.42	0.125	11.58	38.09	•	•	•	•	•	26	200	6.2
RBM5015S				6.0	0.09	4000	3.43	0.097	7.41	31.40	•	•	•	•	•			
RBL5015S				8.0	0.05	3000	2.47	0.069	3.52	23.97	•	•	•	•	•			
RBH5015B	Ball			6.0	0.14	5000	4.42	0.125	11.58	38.09	•	•	•	•	•			
RBM5015B				6.0	0.09	4000	3.43	0.097	7.41	31.40	•	•	•	•	•			
RBL5015B				8.0	0.05	3000	2.47	0.069	3.52	23.97	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
12V	•	•	•	•

