



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH5015S5	Sleeve	B	5	3.5	0.33	5500	10.82	0.306	3.60	30.75	•	•		•	•	31	200	7.5
RDM5015S5				3.5	0.25	5000	9.79	0.277	3.02	28.21	•	•		•	•			
RDL5015S5				3.5	0.20	4500	8.92	0.253	2.56	25.95	•	•		•	•			
RDH5015B5	Ball			3.5	0.33	5500	10.82	0.306	3.60	30.75	•	•		•	•			
RDM5015B5				3.5	0.25	5000	9.79	0.277	3.02	28.21	•	•		•	•			
RDL5015B5				3.5	0.20	4500	8.92	0.253	2.56	25.95	•	•		•	•			
RDH5015S	Sleeve	12	12	6.0	0.16	5500	10.82	0.306	3.60	30.75	•	•		•	•			
RDM5015S				6.0	0.14	5000	9.79	0.277	3.02	28.21	•	•		•	•			
RDL5015S				6.0	0.12	4500	8.92	0.253	2.56	25.95	•	•		•	•			
RDH5015B	Ball			6.0	0.16	5500	10.82	0.306	3.60	30.75	•	•		•	•			
RDM5015B				6.0	0.14	5000	9.79	0.277	3.02	28.21	•	•		•	•			
RDL5015B				6.0	0.12	4500	8.92	0.253	2.56	25.95	•	•		•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V				
12V	•	•	•	•

