



| Listed Model | Bearing System | Housing Type | Rated Voltage | Startup Voltage | Rated Current | Speed | Air Flow | Air Flow | Static Pressure | Noise Level | Motor Protection | | | | | Weight Gram | Packing | |
|--------------|----------------|--------------|---------------|-----------------|---------------|-------|----------|----------|--------------------|-------------|----------------------|------------|-----------------------|--------------|-------------------|-------------|-------------------|--------------|
| | | | VDC | VDC | A | RPM | CFM | CMM | mmH ₂ O | dBA | Resistance Protected | Auto Start | Thermal Speed Control | Alarm Output | Tachometer Output | | Qty./Ctn Purchase | G.W./Ctn Kgs |
| RDH5210S | Sleeve | B | 12 | 6.0 | 0.14 | 6000 | 12.68 | 0.359 | 3.48 | 35.24 | • | • | | • | • | 22 | 600 | 14.7 |
| RDM5210S | | | | 6.0 | 0.12 | 5000 | 10.48 | 0.296 | 2.51 | 30.52 | • | • | | • | • | | | |
| RDL5210S | | | | 6.0 | 0.09 | 4000 | 8.23 | 0.233 | 1.66 | 25.01 | • | • | | • | • | | | |
| RDH5210B | Ball | | | 6.0 | 0.14 | 6000 | 12.68 | 0.359 | 3.48 | 25.24 | • | • | | • | • | | | |
| RDM5210B | | | | 6.0 | 0.12 | 5000 | 10.48 | 0.296 | 2.51 | 30.52 | • | • | | • | • | | | |
| RDL5210B | | | | 6.0 | 0.09 | 4000 | 8.23 | 0.233 | 1.66 | 25.01 | • | • | | • | • | | | |

SAFETY APPROVALS (安規認證)

| | CE | UL | CUL | TUV | CSA |
|-----|----|----|-----|-----|-----|
| 12V | • | • | • | • | • |

