



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH6010S5	Sleeve	H	5	3.5	0.35	4200	18.50	0.523	3.28	31.41	•	•		•	•	23	300	8.7
RDM6010S5				3.5	0.22	3600	15.94	0.451	2.53	27.69	•	•		•	•			
RDL6010S5				3.5	0.17	3000	13.22	0.374	1.84	23.83	•	•		•	•			
RDH6010B5	Ball			3.5	0.35	4200	18.50	0.523	3.28	31.41	•	•		•	•			
RDM6010B5				3.5	0.22	3600	15.94	0.451	2.53	27.69	•	•		•	•			
RDL6010B5				3.5	0.17	3000	13.22	0.374	1.84	23.83	•	•		•	•			
RDH6010S	Sleeve		12	6.0	0.22	4200	18.50	0.523	3.28	31.41	•	•		•	•			
RDM6010S				6.0	0.17	3600	15.94	0.451	2.53	27.69	•	•		•	•			
RDL6010S				6.0	0.14	3000	13.22	0.374	1.84	23.83	•	•		•	•			
RDH6010B	Ball			6.0	0.22	4200	18.50	0.523	3.28	31.41	•	•		•	•			
RDM6010B				6.0	0.17	3600	15.94	0.451	2.53	27.69	•	•		•	•			
RDL6010B				6.0	0.14	3000	13.22	0.374	1.84	23.83	•	•		•	•			
RDH6010S2	Sleeve	24	12.0	0.11	4200	18.50	0.523	3.28	31.41	•	•		•	•				
RDM6010S2			12.0	0.09	3600	15.94	0.451	2.53	27.69	•	•		•	•				
RDL6010S2			12.0	0.07	3000	13.22	0.374	1.84	23.83	•	•		•	•				
RDH6010B2	Ball		12.0	0.11	4200	18.50	0.523	3.28	31.41	•	•		•	•				
RDM6010B2			12.0	0.09	3600	15.94	0.451	2.53	27.69	•	•		•	•				
RDL6010B2			12.0	0.07	3000	13.22	0.374	1.84	23.83	•	•		•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V				
12V	•	•	•	•
24V				

