



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH6020S	Sleeve	H	12	6.0	0.16	4200	22.36	0.633	4.70	31.90	•	•	•	•	•	50	200	11.5
RDM6020S				6.0	0.12	3500	18.56	0.525	3.36	27.21	•	•	•	•	•			
RDL6020S				6.0	0.08	3000	15.75	0.446	2.47	24.12	•	•	•	•	•			
RDH6020B	Ball			6.0	0.16	4200	22.36	0.633	4.70	31.90	•	•	•	•	•			
RDM6020B				6.0	0.12	3500	18.56	0.525	3.36	27.21	•	•	•	•	•			
RDL6020B				6.0	0.08	3000	15.75	0.446	2.47	24.12	•	•	•	•	•			
RDH6020S2	Sleeve	H	24	12.0	0.13	4200	22.36	0.633	4.70	31.90	•	•	•	•	•	50	200	11.5
RDM6020S2				12.0	0.10	3500	18.56	0.525	3.36	27.21	•	•	•	•	•			
RDL6020S2				12.0	0.08	3000	15.75	0.446	2.47	24.12	•	•	•	•	•			
RDH6020B2	Ball			12.0	0.13	4200	22.36	0.633	4.70	31.90	•	•	•	•	•			
RDM6020B2				12.0	0.10	3500	18.56	0.525	3.36	27.21	•	•	•	•	•			
RDL6020B2				12.0	0.08	3000	15.75	0.446	2.47	24.12	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V						•

