



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH7015S	Sleeve	H	12	6.0	0.35	4200	32.50	0.920	4.34	36.01	•	•	•	•	•	48	200	10.6
RDM7015S				6.0	0.25	3600	27.29	0.772	3.23	31.98	•	•	•	•	•			
RDL7015S				6.0	0.16	3000	22.24	0.629	2.27	27.85	•	•	•	•	•			
RDH7015B	Ball			6.0	0.35	4200	32.50	0.920	4.34	36.01	•	•	•	•	•			
RDM7015B				6.0	0.25	3600	27.29	0.772	3.23	31.98	•	•	•	•	•			
RDL7015B				6.0	0.16	3000	22.24	0.629	2.27	27.85	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL
12V	•	•	•

