



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RBH8025S1	Sleeve	A	12	6.0	0.23	3000	10.37	0.293	9.63	35.59	•	•	•	•	•	75	80	6.8
RBM8025S1				6.0	0.16	2500	8.66	0.245	6.40	31.74	•	•	•	•	•			
RBL8025S1				6.0	0.13	2000	6.99	0.197	3.75	25.06	•	•	•	•	•			
RBH8025B1	Ball			6.0	0.23	3000	10.37	0.293	9.63	35.59	•	•	•	•	•			
RBM8025B1				6.0	0.16	2500	8.66	0.245	6.40	31.74	•	•	•	•	•			
RBL8025B1				6.0	0.13	2000	6.99	0.197	3.75	25.06	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
12V	•	•	•	•

